

Benchmark**BMG456**

NITRILE, POWDER-FREE, SINGLE USE GLOVE

Lightweight, powder-free, single-use gloves with textured fingertips.

FEATURES

- › 100% premium quality nitrile, thickness 0.1mm
- › Textured finish on the fingertips to enhance grip
- › Lightweight and comfortable with a 'second skin' feel
- › Powder-free, non-sterile
- › Conforms to EN455 (parts -1, -3 &-4)
- › Category III
- › AQL 4.0
- › Latex free
- › Beaded cuff
- › Thickness 0.10mm (5g)



SUITABLE FOR


Typical Industries

- Aerospace
- Chemical
- Electronics
- Food
- Pharmaceutical
- Manufacturing
- Oil and Gas

Suitable Applications

- Chemical Handling
- Food Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION



See overleaf for explanation

Benchmark**BMG456****PRODUCT INFORMATION**

MATERIALS	LINER:	Nitrile
	COATING:	–
COLOUR	Blue	
LENGTH (mm)	240 mm	
CUFF STYLE	Beaded	

RECOMMENDATIONS FOR USE

- **USE:** Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
6½-7/S	BMG00456DD	100 singles per box
7½-8/M	BMG00456DF	
8½-9/L	BMG00456DH	10 boxes per case
9½-10/XL	BMG00456DJ	

CERTIFICATION LEGENDS**RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016**

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%	B	≥30 min for at least 3 chemicals
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid	C	≥10 min for at least 1 chemical
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide		
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

**PROTECTION AGAINST MICRO-ORGANISMS EN 374-5**

VIRUS = Glove has passed ISO 16604: 2004 (method B)

**FOOD CONTACT DIRECTIVE 2002 / 72 EC**

EN455-1:	Freedom from holes
EN455-2:	Physical properties
EN455-3:	Biological evaluation
EN455-4:	Shelf Life



W W W . l a b t e a m e t . c o m

Labutrusting • Service • Kvalitet

LabTeam Scandinavia AB
 Adress Vasatorpsvägen 1
 SE-254 57 Helsingborg Sverige

Telefon
 Direkt 042-300 91 32
 Kundtjänst 042-300 91 30
 Stockholm 08-400 200 42
 Göteborg 031-277 001
 Danmark 36 98 02 30

Mail labteamet@labteamet.com
Order order@labteamet.com
Service service@labteamet.com

Web
 www.labteamet.com