# Benchmark

# **BMG425**



# NITRILE, POWDER-FREE, SINGLE USE PROTECTION

Lightweight, powder-free, single-use gloves with textured fingertips.

### FEATURES

- > 100% premium quality nitrile
- > Textured finish on the fingertips to enhance grip
- > Lightweight and comfortable with a 'second skin' feel
- > Powder-free, non-sterile
- > Category III
- > AQL 2.5
- > Latex free
- > Beaded cuff
- > Thickness 0.07mm (3.5g)
- > Conforms to EN455 (parts -1, -3 &-4)



## SUITABLE FOR

### **Typical Industries**


### Maintenance

- Automotive
- Manufacturing
- Engineering
- Repair and Finishing

**Suitable Applications** 

- Handling Oily Components
- Janitorial
- Light Assembly

## CERTIFICATION



See overleaf for explanation

# **Benchmark**

# **BMG425**



#### **PRODUCT INFORMATION**

	LINER:	Nitrile
MATERIALS	COATING:	-
COLOUR	Blue	
LENGTH (mm)	240 mm	
CUFF STYLE	Beaded	

#### **ORDERING DETAILS**

SIZE	CODE	PACKAGING
7½-8/M 8½-9/L	BMG00425DF BMG00425DH	100 singles per box
91⁄2-10/XL	BMG00425DJ	10 boxes per case

#### **RECOMMENDATIONS FOR USE**

- USE: Single use glove. Not suitable for thermal, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

### **CERTIFICATION LEGENDS**

CODE

F

D

G

н



## **RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016**

CODE

М Ν

0

Ρ

S

CHEMICAL Methanol Acetone Acetonitrile Dichloromethane Carbon Disulfide

Toluene Diethylamine Tetrahydrofurane Ethyl acetate

EN455-1:	Freedom from holes
EN455-2:	Physical properties
EN455-3:	Biological evaluation
EN455-4:	Shelf Life

n-Heptane Sodium hydroxide 40% Sulphuric acid 96% 65% Nitric acid 99% Acetic acid 25% Ammonium hydroxide 30% Hydrogen peroxide

CHEMICAL

40% Hydrofluoric acid 37% Formaldehyde

E OF VES	BREAKTHROUGH TIME
A	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
с	≥10 min for at least 1 chemical

TYF GL0



**PROTECTION AGAINST** MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)

	1	
)(		

FOOD CONTACT DIRECTIVE 2002 / 72 EC



LabTeam Scandinavia AB Adress Vasatorpsvägen 1 SE-254 57 Helsingborg Sverige

Telefon Direkt 042-300 91 32 Kundtjänst 042-300 91 32 Kundtjänst 042-300 91 30 Stockholm 08-400 200 42 Göteborg 031-277 001 Danmark 36 98 02 30

Mail labteamet@labteamet.com Order order@labteamet.com Service service@labteamet.com

Web www.labteamet.com

EU compliance certificate delivered by the notified body ITS Testing Services UK Ltd, Centre Court, Meridian Business Park, Leicester, LE19 1WD, United Kingdom (Notified Body No 0362)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Labutrustning • Service • Kvalitet