

CO₂ INDOOR AIR QUALITY ANALYSER

This CO₂ analyser is designed to monitor CO₂ for all indoor air quality applications. The unit has been developed to incorporate the latest technology and specification requirements, that provide the user with a fast, simple-to-use and accurate piece of environmental field kit.

FEATURES

- CO₂ 0-10,000 ppm
- Options for:
 - O₂ 0-100%
 - Dual temperature probes 0 to 50°C
 - Data storage and download
 - Humidity sensor 0-100%

BENEFITS

- Accurate CO₂ readings
- Quick verification of CO₂ levels for site audits
- Time saving with dual temperature probes
- Data logging for long term application
- Easy to read large well lit display
- Built-in gas moisture removal

SECTOR

- CO₂ monitoring

APPLICATIONS

- General IAQ
- Environmental site audits
- HVAC System approval
- Illegal immigrant control / detection



© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

POWER SUPPLY		
Battery type	Li Ion	
Battery life	12 hours (10 hours with pump)	
Battery lifetime	600 cycles	
Battery charger	5v DC external power supply and internal charging circuit	
Charge time	4 hours	
Alternative power	5v DC power supply	
GAS RANGES		
Gases measured	CO ₂	By custom dual wavelength infrared cell
	O ₂ (optional)	By internal electrochemical cell
Oxygen cell lifetime	Approximately 3 years in air	
Range	CO ₂	0-10,000 ppm
	O ₂	0-100%
Measurement accuracy*	CO ₂	± 1.5% of range after calibration (typically ± 10 ppm at 500 ppm CO ₂ after user calibration)
	O ₂	± 1.0% of range after calibration
Response time T ₉₀	CO ₂	≤ 20 seconds
	O ₂	≤ 60 seconds
* Plus accuracy of calibration gas used		
FEATURES		
Temperature (optional)	x 2 using optional probes 0°C to +50°C (not available if humidity is selected)	
Temperature accuracy	± 0.2°C	
RH measurement (optional)	RH probe 0 - 100% RH non condensing	
RH accuracy	± 1.5% RH across the range	
Visual and audible alarms	User selectable CO ₂ and O ₂ alarm levels	
Communications	USB type B mini-connector, HID device class	
Data storage	1000 reading sets plus 270 events	
PUMP		
Flow	100 ml / min typically	
ENVIRONMENTAL CONDITIONS		
Operating temperature	0°C to +50°C	
Relative humidity	0 - 95% non condensing (RH probe 0 - 100% non condensing)	
Barometric pressure	500 - 1500 mbar	
IP rating	IP40	
PHYSICAL		
Weight	495 grams	

TECHNICAL SPECIFICATIONS *CONTINUED*

Size	L 165mm, W 100mm, D 55mm
Case material	ABS / polypropylene with silicone rubber inserts
Keys	17 resin capped silicone rubber keys
Display	Liquid crystal display, 128 x 64 pixel With RGB LED backlight
Gas sample filters	Built-in gas dryer tube to remove moisture User replaceable PTFE water trap filter

Note: Due to Geotech's continuous programme of improvement, this specification is subject to change without prior notice

CERTIFICATION

EN 50270:2006	Electromagnetic compatibility - electrical apparatus for the detection and measurement of combustible gases, toxic gases or oxygen
EN 61010-1:2010	Safety requirements for electrical equipment for measurement, control, and laboratory use. Part 1: General requirements