

(+48) 32 453 91 70
info@pol-eko.com.pl

www.pol-eko.com.pl

Data sheet

Cooled Incubator (ST) ST 2/2 Smart PRO



The photo above is for reference only, may show additional options not included in standard equipment. The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

Advantages of the SMART PRO controller:

- large (7"), clear, full colour touch screen
- LAN, USB ports and WiFi for communication and data transfer
- multi-segment time and temperature programs
- overview of data in tabular and graphic form
- visual and sound alarm
- Admin function for management
- password protected log-in
- internal memory for programs and data storage
- event registry with user notifications
- LabDesk software and user manual for direct download



Smart PRO - preview screen






TECHNICAL DATA

air convection	forced
chamber capacity [l]	150 / 150
working capacity [I]	122 / 122
controller	microprocessor PID
display	7" full colour touch screen
TEMPERATURE	
temperature range [°C]	+3+70
temperature resolution every [°C]	0,1
temperature fluctuation at 37°C [+/-°C]*	0,3
temperature variation at 37°C [+/-°C]*	0,5
over temperature protection	class 3.3 to DIN 12880
CHAMBER	
door type	solid / glass or double (option) /4/
interior	
P Smart PRO	DIN 1.4301
PS Smart PRO	DIN 1.4301
housing	
P Smart PRO	powder coated sheet
PS Smart PRO	stainless steel polished

overall dims [mm] /1/	
width A	600
height B	1720
depth C	650
internal dims [mm]	
width D	480
width D'	520
height E	660
depth F	420
depth F'	480
depth G	320
height H	440



shelves (standard max)	3 4 / 3 4
max shelf workload [kg] /2/	10
max unit workload [kg]	30 / 30
weight [kg]	109





ELECTRICAL PARAMETERS

voltage**	230V 50-60Hz	
nominal power [W]	500	
refrigerant	R1234ze / GWP=1	
warranty	24 months	
manufacturer	POL-EKO	

all the above technical data refer to standard units (without optional accessories)

* - fluctuation measured in centre of the chamber; in space, variation (K) calculated for chamber as:

K= +/- (T average max. - T average min.) / 2

** - other power supplies on request

1 - depth doesn't include 50 mm of power cable, the width does not include the 20 mm of rubber plug

2 - on uniformly loaded surface

3 - reinforced shelf

4 - additional internal glass door

OPTIONS AND ACCESSORIES

INOX

Order number: */C Internal glass door

Order number: */A

Order number: */P INOX

Order number: */PP



Order number: */PW

 \Diamond

ALU

INOX

Order number: KUW GN*/*

Order number: ST/CHL/SWP ALU

Order number: ST/CHL/SWP INOX

Order number: ST/CHL/SWPN INOX

Order number: ORG-FARM

Stainless steel cuvettes

Perforated shelf

Reinforced shelf

External glass door

Stainless steel wire shelf INOX

Aluminum drawer with powder coated slides

Stainless steel drawer with powder coated slides

Stainless steel drawer with stainless steel slides





Bank: ING BŚ o/Wodzisław Śląski | Nr rachunku: 90 1050 1403 1000 0022 0879 5498 | Nr rej. w BDO 000005609 NIP: 647-216-26-87 | REGON: 276111984 | Sąd Rejonowy w Gliwicach, X Wydział Gospodarczy | KRS 0001009595



*


+ ||

Order number: *PLUS	Automatic defrosting function
Order number: PT 100	Additional temperature sensor



Order	number:	GNZ

>0<



4

ALARM



USB



20mm

30mm

60mm

100mm

(((●)))



Order number: PORT ALARM

Order number: BPP 12

Order number: LANK

Order number: OCZ/20

Order number: OCZ/30

Order number: OCZ/60

Order number: OCZ/100

Order number: KD

Order number: CCTV



Order number: CCTV CAM

Internal socket

Calibration and IQ, OQ, PQ qualification

Battery backup for display

Dry alarm contact

USB cable

LAN cable

Non-standard access port 20 mm

Additional access port 30 mm

Non-standard access port 60 mm

Non-standard access port 100 mm

Access control

Camera inside the chamber

Additional camera

