# Pharmacy Connect Refrigerator

## with Cloud Connectivity

#### 158L Pharmacy Connect Upright Fridge with Solid Door

GDMAcode	2
SKU code	

PCSR158CT-DWP-UK





#### Key features

- ✓ Remote temperature recording and adjustment
- ✓ Power failure alarm with backup battery powered recording

#### Cloud Connected Controller

Remote temperature monitoring, adjustment, and alarm history via encrypted secure cloud storage over a wireless or Bluetooth connection. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of a power outage.

## Smartphone App & Online Portal

Contactless remote monitoring of air and load temperatures via smart phone app or online portal. Schedule automatic temperature reports that can be downloaded directly to your device.

## Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



✓ Solid and glass door options

performance

✓ Intelligent fan management system for enhanced

## Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.



## Calibration Certified

All Pharmacy Connect appliances come complete with a calibration certificate, prevalidated using UKAS traceable equipment.



The Experts in Medical Refrigeration

1of2

#### Specification: 158L Pharmacy Connect Upright Fridge with Solid Door

Des Segurity Streng     Del.       Dels Extensil Volger Imm)     Golderm       Viel Extensil Volger Imm)     Golderm       Dels Extensil Volger Imm)     Golderm       Status It Viel Extensil Volger Imm<	Gross Capacity (litres)	158L
Unit Birstant Jogit FromPiperineUnit Birstant Jogit From4400000000000000000000000000000000000		
Unit Enserrational post from6.000000000000000000000000000000000000		
Unit ExtensionBitcherminDataset Weigh (mod)3.5.3.4.3.4.3.4.3.4.3.4.3.4.3.4.3.4.3.4.		
Packet With (m)4 5/4/gRedet With (m)6 6/6/m1Redet With (m)6 6/6/m1Redet With (m)10/5/m1Redet With (m)10/5/m1Redet With (m)0.5/m1Scatter of Pain0.5/m1Scatter of P		
Packed Weight mon)6.6.0mmPacked Fight mon)6.9.0mmPacked Fight mon)7.9.0mmPacked Fight mon)7.9.0mmPacked Fight mon)7.9.0mmPacked Packed Pac		
Backs Depin tron)640mmPacks Height Tool000mmPacks Height Tool <th></th> <th></th>		
Backer Weight (mol)J (mm.)Cautory of vigoG.72 Gkg.Cautory of vigoG.72 Gkg.Cautory of vigoG.72 Gkg.ColorM.72 Gkg.ColorM.72 Gkg.ColorM.72 Gkg.ColorP.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color Gkg.S.81 Gkg.Color Gk		
Packer Workpit bajSTP bitsInternal Dismakois (and) MODH]JUDIN in Keyermin Key		
Control provides(N°Internal Directions (Internal Vestors)(2000)Internal Directions (Internal Vestors)(2000)Colur(200		
International proof (Notice)Section 1CalourC		
Temperature Bane		
CalourChinal relationWhite/greenEnsume lensingHistons StealInterner Ishih111557Tore of platesSis Sis Oct Histons StealDoor FindsSis Sis Oct Histons StealDoor FindsSis Sis Oct Histons StealDoor FindsHistons StealDoor FindsHistons StealDoor Gran Of TrysName of Door TrysNumber of Door Trys PositionsName of Door TrysDoor Gran Of TrysName of Door TrysNumber of Door StealName of Door TrysOne Or Gran Of StrainYes JackBoor Gran Of StrainYes JackOne Or Gran Of StrainYes JackOne Or Gran Of StrainYes JackDoor Gran		
Examel InlinkParted StellType of plankBH200 (PH2/BH2 mA)Oper TopicStell200 (PH2/BH2 mA)Door TopicStell20 (PH2/BH2 mA)Nomber of Door TopicPh2/BH2 mA)Nomber of Door TopicPh2/BH2 mA)Door Good Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20PH2/BH2Open Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Open Door Stell20YesDoor Stel		
internal finithHHP*Doer finithSPLB200 (HES/ABS mig)Doer finithParined Stable/SolidDoer finithSpLB4/ClassDoer finithFilinget ReversiteDoer finithFilinget ReversiteDoer finithRelDoer finithRelSolid / ClassRelNorther of Doer TingeRelSolid StableNoDoer tinerRelSolid StableNoReplement Doer SeelYesDoer StableYesDoer StableYesDoer Seel StableNoReplement Doer SeelYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesStable AlerneYesTemperature Doer Stable OneYesTemperature Doer Stable OneYesStable AlerneYesStable AlerneYesTemperature Doer Stable OneYesStable AlerneYesStable AlerneYes <t< th=""><th></th><th></th></t<>		
Type of plashieSPL 800 (HP4585 m/m)Door TinksPlanted Steel / SolidDoor TinksSolid / Clisss.Door TaysSolid / Clisss.Door TaysFile (Steel / Solid / Clisss.)Door TaysNumber of Door Tays PacificanNumber of Door TaysNumber of Door Tays PacificanNumber of Door TaysNumber of Door TaysYes 2 MoresPactode LossNeg		
base rinkihPeinred Statie/ SolidBort TypeSolid / ClarksBort SykInged, RunkershikBort SykNumber of Door TragNumber of Door TragNumber of Door TragNumber of Door TragNumber of Door TragBort SykNumber of SykBort SykNumber of SykBort SykNumber of SykBort SykNumber of SykSykNumber of SykSykNumber of SykBort SykNumber of SykSykNumber of Sy		
Deer typeSoled/OpsyDeer typeFigueDeer typeFigueNumber of Door Tryp PatilonsNNumber of Door Tryp PatilonsNBead concerpson Deprint PatheticsNReplacement Door SeelNBead concerpson Deprint PatheticsNReplacement Door SeelNBead concerpson Deprint Door SeelNReplacement Door SeelN <th></th> <th></th>		
Door StyleHinge Hinge HingeNumber of Door TrysNameNumber of Door TrysNameNumber of Door TrysNameNumber of Door TrysNameNumber of Door StylestionsNameDoor Open StylestionsNameDoor StansorNameDoor StansorNameStansorNameStansorNameStansorNameDoor StansorNameDoor StansorName<		
Doer lane"PartNumber of Door Tray PositionsNANumber of Door Tray PositionsNABealescenter Door SealYesDoor Open Door SearYesGene Door SearsYesLockYesAdvalable Feet fummer & positionsYesBerthole SizeYesBerthole SizeYesDrower Size (mol Woch)YesDrower Size (mol Woch)Yes		
Number of Door Tryp     N/0       Number of Door Tryp Stabilins     N/0       Door Oper Depth (mm)     N/0       Door Oper Sensor     Ves.       Open Door Sensor     Ves.       Lock     Ves.       Open Door Sensor     Ves.       Lock     Ves.       Adjustable Feet (number & position)     4.Al.Algustable       Dorthole Location     Reproduct Adjustable       Dorthole Location     Reproduct Adjustable       Temperature Dipply on Panel     Ves.       Temperature Disply on Panel     Ves.       Temperature Disply on Panel     Ves.       Number of Shelf Positions     Ves.       Shelf Adam Contactis     Ves.       Number of Shelf Positions     Yes.       Shelf Adarial     Ves.       Draver Statin (Wochd)     Adjustable       Draver Statin (Wochd)     Notaction       Draver Statin (Wochd)     Notaction       Draver Statin (Wochd)     Notaction       Draver Statin (Wochd)     Notaction       Draver Statin (Notachi)     Notaction       Draver Statin (Notachi)     Notaction<		
Number of box Tray bashionsNyBeplexement Door SealNy6.Beplexement Door SealYes.Box Door Searsont Door SealYes.Gone Door Searsont Door SealYes.Seal Control SealYes.Borthol SizeYes.Borthol SizeBortholBorthol SizeBortholBorthol SizeBortholBorthol SizeYes.Borthol Size <t< th=""><th></th><th></th></t<>		
Door Open Depth (mm)IBDnmReplement Door SalorYesOpen Door SanorYesAdjustable Feet (number & position)4.4.1.4.1.5.1.5.1.5.1.5.1.5.1.5.1.5.1.5.		
Replexement Door Seal     Yes       Open Door Senor     Yes       Lack     Yes, 2 Keys       Adjustable Fer, Gimber & Spotton     A All adjustable Rev       Porthole     Yes       Porthole Size     Ib mm       Porthole Size     Yes       Remote Alarm Constas     Yes       Number of Stables/Dravers     4       Number of Stables/Dravers     4       Number of Stables/Dravers     7       Sheff Size (rm) (WxDzH)     Ib Methode       Draver Statis (rm) (WxDzH)     Ib Methode       Draver Statis     Ib Polythene Coated Wire       Draver Statis     Ib Methode       Draver Statis     Ib Polythene Coated Wire       Draver S		
Open Door SensorYesLockYes, 2 KeyaAdjustable Fest (number & position)A Al AdjustablePorthole StarIf mmPorthole StarIf mmPorthole StarIf mmPorthole StarIf mmTemperatura Diplay on PanelYesTemperatura Display on FanelYesTemperatura Display on FanelYesTemperatura Display on FanelYesRemeta AdamYesRemeta AdamYesRemeta AdamYesNumber of ShelveSDawers4Number of ShelveSDawers4Number of ShelveSDawers4Number of ShelveSDawers6Shelf Star (mm) (Mobd)Polythene Coated WireDowers Star (mm) (Mobd)NoDowers Star (mm) (Mobd)NoDowers Star (mm) (Mobd)NoDataset Star (mm) (Mobd)No		
LockWys.2 KeysAdutable Fer (Imper & position)4.4 Ind vig/xabbleBorthole Size16 mmBorthole Size19 mmBorthole Size19 mmSize Size Size Size Size Size Size Size	•	
Adjustable     All adjustable       Porthole     Ves       Porthole Size     IS mm       Porthole Size     Borthole       Porthole Size     Borthole       Temperature Dipoly on Puel     Yes       Temperature Dipoly on Puel     Yes       Remote Alum Contacts     Yes       Remote Alum Contacts     Yes       Number of Shube/Showers     4       Number of Shube/Showers     5       Sheff Material     Polythener Contacts       Number of Shube/Showers     4       Number of Shube/Showers     5       Sheff Material     Polythener Contact Wire       Drawer Material     Nomber of Shube/Shom Xfirm       Drawer Size (mm) (Wobdh)     Polythener Contact Wire       Drawer Size (mm) (Wobdh)     Yes	•	
Decthole     Yes       Borthole iscation     Bern M       Borthole iscation     Fear Bortom       Borthole iscation     Yes       Temperature Diagno Phanel     Yes       Temperature Alarm     Yes       Borthole iscontacts     Yes       Audibe Alarma     Yes       Vauia Marria     Yes       Number of Shelf Positions     4       Shelf Material     Posytheme Casted Wire       Drawer Size (rmm) (WADAH)     Alafferia x 405mm x 6mm       Shelf Material     Polytheme Casted Wire       Drawer Size (rmm) (WADAH)     Alafferia       Drawer Material     Polytheme Casted Wire       Drawer Size (rmm) (WADAH)     Alarma       Drawer Size (rmm) (WADAH)     Alarma       Drawer Size (rmm) (WADAH)     Polytheme Casted Wire       Basket Size (rmm) (WADAH)     Alarma       Drawer Size (rmm) (WADAH)     Alarma       Drawer Size (rmm) (WADAH)     Polytheme Casted Wire       Basket Size (rmm) (WADAH)     Alarma       Drawer Size (rmm) (WADAH)     Yes       Drawer Size (rmm) (WADAH)     Yes       Bas		
perthole SizeIs runPerthole LocalitationRear BrattomTemperature Display on PanelYesTemperature Display on PanelYesTemperature Display on PanelYesTemperature Display on PanelYesTemperature Display on PanelYesRende Alarm ContactsYesAudibe AlarmsYesAudibe AlarmsYesNumber of Shelves/Dravers4Number of Shelves/Dravers4Shelf Sice (nm) (WxDxH)AdStrim x 4dStrim x		
PerthelicationRest BatromTemperature Display on PanelYesTemperature Display on PanelYesRemote Alarm ContatsYesAudible AlarmsYesNumber of SheviewSonwers4Number of SheviewSonwers4Number of SheviewSonwers4Number of SheviewSonwers4Shef Meditions5Shef Steirmon (Wabath)496mm x 405mm x 6mmShef Steirmon (Wabath)496mm x 405mm x 6mmShef Meditions10Shef Meditions10Shef Meditions10Shef Meditions10Shef Meditions10Shef Meditions10Drawer Size (mm) (WADath)10Basket Size (mm) (WADath)10Basket Size (mm) (WADath)10Shef Meditions10Drawer Size (mm) (WADath)10Drawer Size (mm) (WADath)10Basket Size (mm) (WADath)10Basket Size (mm) (WADath)10Drawer Size (mm) (WADath)10Shef MeditionsYesSteir Size (Material)10Basket Size (mm) (WADath)10Basket Size (mm) (WADath)10Size (Size Size		
Temperature Display on PanelYesTemperature Display on PanelYesRemote Jarm ContactsYesRemote Jarm ContactsYesVisual AlarmsYesYaual AlarmsYesNumber of Shafe PationsASheft Size (mm) (WACMI)ASheft Size (mm) (WACMI)Polytheme Coated WireDrawer MaterialPolytheme Coated WireDrawer MaterialPolytheme Coated WireDrawer Size (mm) (WACMI)ABasket MaterialPolytheme Coated WireDrawer Size (mm) (WACMI)ANumber of BasketsPolytheme Coated WireBasket Size (mm) (WACMI)AUpin Patheme Coated WirePolytheme Coated WireBasket Size (mm) (WACMI)AUpin TypeDeor Switch / ControllerUpin TypeDeor Switch / ControllerSpark FreeNoDefort settingDeor Switch / ControllerSpark FreeNoDefort settingYesSpark FreeNoSpark Free <th></th> <th></th>		
Temperature NameYesAudible NamesYesAudible NamesYesAudible NamesYesYesYesYesYesNumber of Shelf Nove/Dravers4Number of Shelf Nove/Dravers4Shelf Saterm(VixOxH)YesShelf Saterm(VixOxH)YesDraver Size (rmm) (VixOxH)YesDraver Size (rmm)YesNome of ProbesZProbe TypeAir & Lord (Slicone Oll)Arribut (rmm)YesNome of ProbesYes		
Benete Alarm Contacts     Yes       Audible Alarms     Yes       Vaual Alarms     Yes       Number of Shelf Positions     4       Number of Shelf Positions     5       Shelf Size (rmn) (WxDxH)     496mm x 405mm x 6mm       Drawer Size (rmn) (WxDxH)     Polythenc Coated Wire       Drawer Size (rmn) (WxDxH)     N/a       Basket Size (rmn) (WxDxH)     485mm x 255mm x 171mm       Basket Size (rmn) (WxDxH)     485mm x 255mm x 171mm       Interior Light     Polythenc Coated Wire       Basket Size (rmn) (WxDxH)     485mm x 255mm x 171mm       Interior Light     Polythenc Coated Wire       Basket Size (rmn) (WxDxH)     485mm x 255mm x 171mm       Interior Light     Polythenc Coated Wire       Basket Size (rmn) (WxDxH)     485mm x 255mm x 171mm       Interior Light     Polythenc Coated Wire       Basket Size (rmn) (WxDxH)     485mm x 255mm x 171mm       Interior Light     Polythen Coated Size       Spark Free     Door Swrkth, / Controller<		
Audible NammeYesNumber of ShellPostes/Dravers4Number of ShellPostes/Dravers4Number of Shell Postions5Shell MaterialPolythene Coated WireDraver Size (mm) (WxDxH)496mm x 405mm x 6mmShell MaterialPolythene Coated WireDraver Size (mm) (WxDxH)1Basket Size (mm) (WxDxH)1Basket Size (mm) (WxDxH)1Basket Size (mm) (WxDxH)495mm x 255mm x 17mmBasket Size (mm) (WxDxH)495mm x 255mm x 17mmBasket Size (mm) (WxDxH)495mm x 255mm x 17mmInterior LightYesLight ActivationDoor Switch / ControllerFanNesSpark FreeNesDefrost Beskt Size (mm) (WxDxH)0Batter Size (mm) (WxDxH)0Spark FreeNesLight ActivationDoor Switch / ControllerFanYesSpark FreeNesDefrost Beskt Up/HoursNesButtery Besk Up/HoursYesSurd FreeYesNifiYesNifiYesAmberi FreeNesNifiYesAmberi FreeYesNifi FreeYesNifi FreeYesNifi FreeYesNifi FreeYesNifi FreeYesAmonis FreeYesStart MaperialYesStart MaperialYesStart MaperialYesStart Start MaperialYesStart Start MaperialYes </th <th></th> <th></th>		
Visual AmmeYesNumber of Sheef Positions4Number of Sheef Positions5Sheff Size (mm) (VisDxH)496/mm x 40mm x 6mmSheff Size (mm) (VisDxH)Polythene Coated WireDrawer Size (mm) (VisDxH)N/ADrawer Size (mm) (VisDxH)N/ADrawer Size (mm) (VisDxH)N/ASalet Size (mm) (VisDxH)1Basket MaterialPolythene Coated WireBasket Size (mm) (VisDxH)485mm x 25mm x 77mmInstroir LightPolythene Coated WireBasket MaterialPolythene Coated WireBasket Size (mm) (WisDxH)485mm x 25mm x 77mmInstroir LightPolythene Coated WireBasket MaterialPolythene Coated WireSpark FreeDoor Switch / ControllerFanYesSpark FreeDoor Switch / ControllerBuetoshYesWiFiYesNerdYesNerdYesNerdYesNerdYesNumber of PolosYesNumber of PolosYes		
Number of Shelves/Dravers4Number of Shelf Positions5Shelf MaterialPolythene Coated WireDraver Size (mm) (WxDxH)Polythene Coated WireDraver Size (mm) (WxDxH)Polythene Coated WireDraver Size (mm) (WxDxH)N/aDraver Size (mm) (WxDxH)Polythene Coated WireBasket Size (mm) (WxDxH)Polythene Coated WireBasket Size (mm) (WxDxH)Polythene Coated WireBasket Size (mm) (WxDxH)VesBasket Size (mm) (WxDxH)VesSprit FreeNoDefore StettingDotor Switch / ControllerFanVesSprit FreeNoDefore StettingAuto (Off Cycle)Controller TypeDigital WiFL, ExternalBattery Back Up/HoursVesWiFIVesNumber of Polos2Probe TypeAif & Load (Silicone Oil)Arbient Temperature RangeNoVesVesWiff EfferedVesWiff InterpretorNoOther Plug Types AvailableVesUK 3 Pin PlugAlon (Silicone Oil)Arbient Temperature RangeNoOther Plug Types AvailableVesUK 3 Pin PlugAlon (Silicone Oil)Other Plug Typ		
Number of Shelf Positions5Shelf Steir (mm) (WxDxH)496mm x 405mm x 6mmDrawer Steir (mm) (WxDxH)Polythene Coated WireDrawer Steir (mm) (WxDxH)N/aDrawer MaterialN/aNumber of Baskets1Basket State (mm) (WxDxH)485mm x 100mmBasket State (mm) (WxDxH)485mm x 25mm x 10mmBasket State (mm) (WxDxH)485mm x 25mm x 10mmInterior LightEDDLight ActivationYesSpark FreeAuto (Off Cycle)Controller TypeDigital WFL, ExternalBastery Bask Up/HoursYesNPCYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYes<		
Shef Ste (mm) (WXDxH)449cmm x 405cmm x 6 mmShef MaterialPolythene Coated WireDrawer Size (mm) (WXDxH)n/aDrawer Size (mm) (WXDxH)n/aDrawer Stex (mm) (WXDxH)n/aBasket Size (mm) (WXDxH)ABset Size (mm) (WXDxH)Basket Size (mm) (WXDxH)ABset Size (mm) (WXDxH)Interior LightYesLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerFanDoor Switch / ControllerFanNoDefors testingALto (Off Cycle)Controller TypeDigital Wire, ExternalBattery Back Up/HoursYes/24hrs TBCBluetoothYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYes <trr>WiFi<th></th><th></th></trr>		
Shef MatrialPolythene Coated WireDrawer Materialn/aNumber of Basketsn/aNumber of Baskets1Basket MaterialPolythene Coated WireBasket MaterialPolythene Coated WireBasket Material485mm x255mm x17mmInterior LightYesLight TypeLEDLight ActwationDoor Switch / ControllerFanDoor Switch / ControllerSpark FreeNoDefrost settingAuto (Cf Cycle)Controller TypeDigital WiFI, ExternalBatter y Back Up/HoursYesButtor De Switch / Controller TypeYesController TypeDigital WiFI, ExternalBattery Back Up/HoursYesButtor TypeYesNine of ProbesYesNine of ProbesYesRefrigerant TypeNoCfC FreeYesHCC FreeYesKCC FreeYesUK3 Fin PlugYesUK3 Fin PlugYesVoltage SupplyYesVoltage SupplyStandKord SuppleYesKord Supple		
Drawer Size (mm) (Wx0xH)     n/a       Drawer Material     n/a       Drawer Material     n/a       Basket Size (mm) (Wx0xH)     Polythene Coated Wire       Basket Size (mm) (Wx0xH)     485mm x 25mm x 77mm       Interior Light     Yes       Light Type     LED       Light Activation     Door Switch / Controller       Fan     Yes - Tangential       Spark Free     No       Defords setting     Auto (Off Cycle)       Controller Type     Digital WiFl, External       Bletcoth     Yes       NFC     Yes       WiFl     Yes       Number of Probes     Yes       Ner     Yes       Number of Probes     Ait & Logo       ViFlo     Ait & Logo       Amber Temperature Bange     10°C: to 32°C       Refrigerant Type     Ait & Logo       KG Free     Yes       MIC Free     Yes       MC Free     Yes       MC Free     Yes       Mark Long Supply     Ait & Long       Mono     Yes		
Drawer Material     n/a       Number of Baskets     1       Basket Material     Polythene Coated Wire       Basket Material     Polythene Coated Wire       Basket Size (mm) (WXXH)     (455mm X77mm)       Interior Light     Ves       Light Type     (ED)       Light Activation     Door Switch / Controller       Fan     Door Switch / Controller       Spark Free     Mon       Defrost setting     Auto (Off Cycle)       Controller Type     Digital Wirle, External       Battery Back Up/Hours     Yes       Battery Back Up/Hours     Yes       NFC     Yes       NiFI     Yes       Number of Probes     2       Probe Type     Air& Load (Silicone Oil)       Ambient Temperature Range     NPC Cot 0.3°C       Refrigerant Type     Yes       Refrigerant Type     Yes <tr< th=""><th></th><th></th></tr<>		
Number of Baskets     1       Basket Material     Polythene Coated Wire       Basket Size (mm) (WxDxH)     A85mm x Z55mm x X71mm       Interior Light     Ves       Light Npe     Door Switch / Controller       Light Activation     Door Switch / Controller       Ean     No       Defrost setting     Auto (Dif Cycle)       Controller Type     Digital WIFL; External       Battery Back Up/Hours     Ves / Tangential       Bluetooth     Ves       NFC     Ves       WIFI     Ves       Number of Probes     2       Probe Type     Air & Load (Silicone Oil)       Ambient Temperature Range     No       Refrigerant Type     PR600a       CFC Free     Ves       MCC Free     Ves       MCC Free     Yes       MCG Yes     Yes       VK3 Pin Plug     No       Other Plug Types Available     Yes       VK3 Pin Plug     No       Other Plug Types Available     Yes       VK3 Pin Plug     Yes       VK3 Pin Plug		
Basket Material     Polythene Coated Wire       Basket Size (mm) (WxDxH)     485mm x 25mm x 171mm       Iterior Light     Q455mm x 25mm x 171mm       Uight Type     Light Coated Wire       Light Ype     Light Coated Wire       Light Activation     Door Switch / Controller       Fan     Door Switch / Controller       Spark Free     No       Defroit setting     Auto (Off Cycle)       Controller Type     Digital WiFl, External       Battery Back Up/Hours     Yees       NFC     Yees       NIFC     Yees       NIFC     Yees       WIFI     Yees       Number of Probes     Q       Ref Spee     Q       Vies     Q       WIFI Conce     Yees       Number of Probes     Q       Ref Spee     Q       Probe Type     Air & Load (Silicore Oil)       Ambient Temperature Range     Yees       MCF C Free     Yees       MCF C Free     Yees       MCF Plug     Yees       MCF Plug Types Available     Yees </th <th></th> <th>l/d</th>		l/d
Basket Size (mm) (WxDxH)485mm x 255mm x 171mmInterior LightYesLight ActivationLEDLight ActivationDoor Switch / ControllerFanObor Switch / ControllerSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeObjital W/FL ExternalBatery Back Up/HoursYes 2BluetoothYesNrCYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Armis Consolier TypeYesBittery Back Up/HoursYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Armis Consolier TypeYesBittery Back Up/HoursYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Armis Consolier TypeYesBrifgerant TypeYesBrifgerant TypeYesMEC FreeYesArmonia FreeYesVoltag SupplyYesVoltag SupplyYesInsulation TypeHigh Density Polyurethane FoarnBilavian Types AvailableYesVoltag SupplyYesSupplica LockPCSR158W/FI-DUK-UK ((444411326))Optional Draver SystemPCSR158W/FI-DUK-UK ((444411326))		Deluthere Cented Wire
Interior LightYesLight ActivationLEDLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerFanYes - TangentialSpark FreeNoDefrost settingAkto (Off Cycle)Controller TypeDigital WIFI, ExternalBattery Back Up/HoursYes/24hrs TBCBluetoothYesNincYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature RangeOiO°C to 32°CRefrigerant TypeYesHCC FreeYesAmoin Temperature RangeYesUS 3 Pi DigNoOther Pilog SupplyYesVoltage Supply220-240VInsulation Tickness (mm)High Density Polywurethane FoamBowing AgentCyclopentaneAnti Microbial HandleYesWall BraketsNoOptional Draver SystemPCSR158WIFI-DLK-UK (444411326)Optional Draver SystemPCSR158WIFI-DLK-UK (444411326)		
Light TypeLEDLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital WIFL, ExternalBattery Back Up/HoursYesBluetoothYesNFCYesWIFIYesProbe TypeAlt & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeYesHFC FreeYesKFCYesWife TreeYesWife TreeYesWife Temperature Range10°C to 32°CRefrigerant TypeYesKFC FreeYesWife TreeYesKFC FreeYesKFC FreeYesVidage SupplyYesWife TreeYesKG Sent Mich Const		
Light Activation Door Switch / Controller   Fan No   Spark Free No   Defrost setting Auto (Off Cycle)   Controller Type Digital WiFl, External   Battery Back Up/Hours Yes/Zehns TBC   Bluetooth Yes   NFC Yes   WiFl Yes   Number of Probes 2   Probe Type Ait's Load (Silicone Oil)   Ambient Temperature Range 10°C' to 32°C   Refrigerant Type Yes   CFC Free Yes   MCC Free Yes   Mired Yes   US 3 Pin Plug Yes   Votage Supply 220-240V   Insulation Trickness (mm) Yes   Insulation Tickness (mm) 45mm   Insulation Tickness (mm) Yes   Optional Digital Lock PCSRISWIFI-DUK / UK (444411323)   Optional Digital Lock PCSRISWIFI-DUK-/UK (444411326)		
PanYes - TangentialSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital WIFI, ExternalBattery Back Up/HoursYes/Zkhrs TBCBluetoothYesNFCYesNFCYesNumber of Pobes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C'c to 32°CRefrigerant TypeR600aCFC FreeYesUK StoreYesURTS The Silicone Oil Digital WIFI (Science Oil)Ambient Temperature RangeR600aCFC FreeYesUK StoreYesUK StoreYes <th></th> <th></th>		
Spark Free   No     Defrost setting   Auto (Off Cycle)     Controller Type   Digital WIFI, External     Battery Back Up/Hours   Yes/24hrs TBC     Bluetooth   Yes     NFC   Yes     Number of Probes   2     Probe Type   Air & Load (Slicone Oll)     Ambient Temperature Range   10°C to 32°C     Refrigerant Type   Refrigerant Type     CFC Free   Yes     HFC Free   Yes     UK 3 Pin Plug   Yes     Other Plug Types Available   Yes     Voltage Supply   220-240V     Insulation Thickness (mm)   High Density Polyurethane Foam     Blowing Agent   Cyclopentane     Antil Kicrobial Handle   Yes     Wall Brackets   No     Optional Digital Lock   PCSR158WIFI-DLK-UK (444411323)		
Defrost setting Auto (Off Cycle)   Controller Type Digital WIFI, External   Battery Back Up/Hours Yes/24/hrs TBC   Bluetooth Yes   NFC Yes   NIFI Yes   Number of Probes 2   Probe Type Alir & Load (Silicone Oil)   Ambient Temperature Range 10% C to 32% C   Refrigerant Type Re6000a   CFC Free Yes   Ammonia Free Yes   UK3 Pin Plug No   Other Plug Type Available Yes   Voltage Supply 220-240V   Insulation Trickness (mm) High Density Polyurethane Foam   Blowing Agent Quectonate   Anti Rotobial Handle Yes   Wall Brackets No   Optional Digital Lock PCSR158WIFI-DLK-UK (444411326)		
Controller TypeDigital WIFI, ExternalBattery Back Up/HoursDigital WIFI, ExternalBattery Back Up/HoursYesBluetoothYesNFCYesWIFIYesNumber of Probes2Probe TypeAlia E Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeRe600aCFC FreeYesHCF CreeYesHCF CreeYesMomoia FreeYesVoltage SupplyNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAntil Kircobial HandleYesWall BracketsNoOptional Digital LockPCSRT58WIFI-DUK-UK (444411326)		
Battery Back Up/Hours   Yes/24hrs TBC     Bluetooth   Yes     NFC   Yes     NFC   Yes     Number of Probes   Yes     Probe Type   Air & Load (Silicone Oil)     Ambient Temperature Range   10%C to 32%C     Refrigerant Type   R600a     CFC Free   Yes     HFC Free   Yes     Momoin Free   Yes     UK 3 Pin Plug   No     Ottar Plug Types Available   Yes     Voltage Supply   220-240V     Insulation Tixkness (mm)   45mm     Insulation Type   High Density Polyurethane Foam     Blowing Agent   Cyclopentane     Anti Kirobial Handle   Yes     Wall Brackets   No     Optional Drawer System   PCSR158WIFI-DWP-UK (444411323)     Optional Digital Lock   PCSR158WIFI-DLK-UK (444411326)		
Bluetooth Yes   NFC Yes   WIFI Yes   WiFi Yes   Number of Probes 2   Probe Type Air & Load (Silicone Oil)   Ambient Temperature Range 10°C to 32°C   Refrigerant Type R600a   CFC Free Yes   HFC Free Yes   HFC Free Yes   Mamonia Free Yes   K3 Din Plug No   Other Plug Types Available Yes   Voltage Supply 220-240V   Insulation Type High Density Polyurethane Foam   Blowing Agent Cyclopentane   Antiderabilit Type No   Optional Drawer System PCSR158WIFI-DWP-UK (444411323)   Optional Digital Lock PCSR158WIFI-DLK-UK (444411326)		
NFCYesWIFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Din PlugNoOttare Plug Types AvailableYesVoltage Supply220-240VInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
WiFiYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesMomoia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DUK-UK (444411326)		
Number of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aHFC FreeYesHFC FreeYesHCFC FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Probe TypeAir & Load [Silicone Oil]Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aCFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DUK-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aHFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DUK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Refrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)		
CFC FreeYesHFC FreeYesArmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnt Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
HFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
HCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Ammonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
UK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Other Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Voltage Supply     220-240V       Insulation Thickness (mm)     45mm       Insulation Type     High Density Polyurethane Foam       Blowing Agent     Cyclopentane       Anti Microbial Handle     Yes       Wall Brackets     No       Optional Drawer System     PCSR158WIFI-DWP-UK (444411323)       Optional Digital Lock     PCSR158WIFI-DLK-UK (444411326)		
Insulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Insulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326)		
Blowing Agent   Cyclopentane     Anti Microbial Handle   Yes     Wall Brackets   No     Optional Drawer System   PCSR158WIFI-DWP-UK (444411323)     Optional Digital Lock   PCSR158WIFI-DLK-UK (444411326)		
Anti Microbial Handle Yes   Wall Brackets No   Optional Drawer System PCSR158WIFI-DWP-UK (444411323)   Optional Digital Lock PCSR158WIFI-DLK-UK (444411326)		Lligh Danaity Daly wrath and Faana
Wall Brackets     No       Optional Drawer System     PCSR158WIFI-DWP-UK (444411323)       Optional Digital Lock     PCSR158WIFI-DLK-UK (444411326)	Insulation Type	
Optional Drawer System     PCSR158WIFI-DWP-UK (444411323)       Optional Digital Lock     PCSR158WIFI-DLK-UK (444411326)	Insulation Type Blowing Agent	Cyclopentane
Optional Digital Lock PCSR158WIFI-DLK-UK (444411326)	Insulation Type Blowing Agent Anti Microbial Handle	Cyclopentane Yes
	Insulation Type Blowing Agent Anti Microbial Handle	Cyclopentane Yes No
	Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	Cyclopentane Yes No PCSR158WIFI-DWP-UK (444411323)
	Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	Cyclopentane Yes No PCSR158WIFI-DWP-UK (444411323)



The Experts in Medical Refrigeration

www.lec-medical.co.uk 💊 0344 815 3742