Pharmacy Plus Bluetooth Enabled Refrigerator

158L Pharmacy Plus Upright Fridge with Glass Door

GDMAcode	PPGR1
SKU code	444411

PGR158BT-UK





Key features

- \checkmark Local monitoring and alarm history via Bluetooth
- \checkmark Power failure alarm with backup battery powered recording
- \checkmark Solid and glass door options

 \checkmark Intelligent fan management system for enhanced performance



Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.



Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



Specification: 158L Pharmacy Plus Upright Fridge with Glass Door

Gross Capacity (litres)	158L
Net Capacity (litres)	154L
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Unit External Height (mm)	850mm
Product Weight (kg)	33.25kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	910mm
Packed Weight (kg)	37.82Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	500mm x 450mm x 725mm
Temperature Range	+2°C to +8°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	n/a
Number of Door Tray Positions	n/a
Door Open Depth (mm)	1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	4 All adjustable
Porthole	Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	4
Number of Shelf Positions	5
Shelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 255mm x 171mm
Interior Light	Yes
Light Type	LED Dear Guiteb (Controller
Light Activation Fan	Door Switch / Controller
Spark Free	Yes - Tangential No
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	No
Bluetooth	Yes
NFC	Yes
WIFI	No
Number of Probes	2
Probe Type	Air & Load (Silicone Oil)
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	No
Other Plug Types Available	Yes
	220-240V
Voltage Supply	
	45mm
Voltage Supply	45mm High Density Polyurethane Foam
Voltage Supply Insulation Thickness (mm)	
Voltage Supply Insulation Thickness (mm) Insulation Type	High Density Polyurethane Foam
Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent	High Density Polyurethane Foam Cyclopentane
Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	High Density Polyurethane Foam Cyclopentane Yes
Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle	High Density Polyurethane Foam Cyclopentane Yes No
Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	High Density Polyurethane Foam Cyclopentane Yes No No

