

Pharmacy Plus Bluetooth Enabled Refrigerator

158L Pharmacy Plus Upright Fridge with Solid Door

GDMA code PPSR158BT-UK
 SKU code 444411308



Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- ✓ Solid and glass door options
- ✓ Intelligent fan management system for enhanced performance



Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.

Specification: 158L Pharmacy Plus Upright Fridge with Solid Door

| | |
|-------------------------------------|--------------------------------|
| Gross Capacity (litres) | 158L |
| Net Capacity (litres) | 154L |
| Unit External Width (mm) | 595mm |
| Unit External Depth (mm) | 660mm |
| Unit External Height (mm) | 850mm |
| Product Weight (kg) | 33.25kg |
| Packed Width (mm) | 640mm |
| Packed Depth (mm) | 660mm |
| Packed Height (mm) | 910mm |
| Packed Weight (kg) | 37.82Kg |
| Country of Origin | UK |
| Internal Dimensions (mm) (WxDxH) | 500mm x 450mm x 725mm |
| Temperature Range | +2°C to +8°C |
| Colour | White/green |
| External Finish | Painted Steel |
| Internal Finish | HIPS* |
| Type of plastic | SRL800 (HIPS/ABS mix) |
| Door Finish | Painted Steel / Solid |
| Door Type | Solid |
| Door Style | Hinged, Reversible |
| Door Liner | Flat |
| Number of Door Trays | n/a |
| Number of Door Tray Positions | n/a |
| Door Open Depth (mm) | 1150mm |
| Replacement Door Seal | Yes |
| Open Door Sensor | Yes |
| Lock | Yes, 2 Keys |
| Adjustable Feet (number & position) | 4 All adjustable |
| Porthole | Yes |
| Porthole Size | 16 mm |
| Porthole Location | Rear Bottom |
| Temperature Display on Panel | Yes |
| Temperature Alarm | Yes |
| Remote Alarm Contacts | Yes |
| Audible Alarms | Yes |
| Visual Alarms | Yes |
| Number of Shelves/Drawers | 4 |
| Number of Shelf Positions | 5 |
| Shelf Size (mm) (WxDxH) | 496mm x 405mm x 6mm |
| Shelf Material | Polythene Coated Wire |
| Drawer Size (mm) (WxDxH) | n/a |
| Drawer Material | n/a |
| Number of Baskets | 1 |
| Basket Material | Polythene Coated Wire |
| Basket Size (mm) (WxDxH) | 485mm x 255mm x 171mm |
| Interior Light | Yes |
| Light Type | LED |
| Light Activation | Door Switch / Controller |
| Fan | Yes - Tangential |
| Spark Free | No |
| Defrost setting | Auto (Off Cycle) |
| Controller Type | Digital BT, External |
| Battery Back Up/Hours | No |
| Bluetooth | Yes |
| NFC | Yes |
| WIFI | No |
| Number of Probes | 2 |
| Probe Type | Air & Load (Silicone Oil) |
| Ambient Temperature Range | 10°C to 32°C |
| Refrigerant Type | R600a |
| CFC Free | Yes |
| HFC Free | Yes |
| HCFC Free | Yes |
| Ammonia Free | Yes |
| UK 3 Pin Plug | No |
| Other Plug Types Available | Yes |
| Voltage Supply | 220-240V |
| Insulation Thickness (mm) | 45mm |
| Insulation Type | High Density Polyurethane Foam |
| Blowing Agent | Cyclopentane |
| Anti Microbial Handle | Yes |
| Wall Brackets | No |
| Optional Drawer System | No |
| Optional Digital Lock | No |
| Other Door Option | Glass PPGR158BT-UK |