Pharmacy Plus Bluetooth Enabled Refrigerator

400L Pharmacy Plus Upright Fridge with Solid Door

GDMAcode PPSR400BT SKU code 444411317





Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- \checkmark Solid and glass door options

✓ Intelligent fan management system for enhanced performance



Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.



Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.



Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



The Experts in Medical Refrigeration

www.lec-medical.co.uk

Specification: 400L Pharmacy Plus Upright Fridge with Solid Door

Gross Capacity (litres)	394L
Net Capacity (litres)	394L 389L
Unit External Width (mm)	595mm
Unit External Depth (mm)	660mm
Unit External Height (mm)	1935mm
Product Weight (kg)	61.8Kg
Packed Width (mm)	640mm
Packed Depth (mm)	660mm
Packed Height (mm)	1995mm
Packed Weight (kg)	70.8Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	515mm x 480mm x 1783mm
Temperature Range	+2°C to +8°C
Colour	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Flat
Number of Door Trays	n/a
Number of Door Tray Positions	n/a
Door Open Depth (mm)	11/a 1150mm
Replacement Door Seal	Yes
Open Door Sensor	Yes
Lock	Yes Yes, 2 Keys
LOCK Adjustable Feet (number & position)	2 adjustable (front)
Porthole	Z adjustable (iront) Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	7
Number of Shelf Positions	12
Shelf Size (mm) (WxDxH)	496mm x 405mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	1
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 255mm x 171mm
Interior Light	Yes
Light Type	LED
Light Activation	Door Switch / Controller
Fan	Yes - Tangential
Spark Free	no
Defrost setting	Auto (Off Cycle)
Controller Type	Digital BT, External
Battery Back Up/Hours	no
Bluetooth	Yes
NFC	Yes
WIFI	no
Number of Probes	2
Probe Type	Air & Load (Silicone Oil)
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	no
Other Plug Types Available	Yes
Voltage Supply	220-240V
Insulation Thickness (mm)	45mm
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes
Wall Brackets	No
	No
Optional Drawer System	
Optional Drawer System Optional Digital Lock Other Door Option	No Class - PPSR400BT (444411316)

